

Megapixel HD IP IR Bullet Camera (42IR LED)

Model No.: CV-XIP628HW26K



Main feature:

- Professional design for HD network camera, small, beautiful and delicate, best for home security.
- Material: aluminum alloy, innovative patented heat dissipation structure, make HD camera can works well under high temperature.
- 8.0MP 4k , H.265+,MStar328Q+Sony 415, 1/2.8" CMOS
- Advanced digital signal processing technology, high brightness imported SMT IR source, show the best HD video effects in both day and night environment.
- 8.0 Megapixel HD CS lens+ IR-CUT auto switch in day and night,4mm,6mm fixed focus lens optional
- 42PCS IR LED, effective night vision distance is 40m, excellent performance in dark environment.
- Support 3D DNR, auto white balance, auto electronic shutter, auto electronic gain, real color reproduction, high resolution image.
- ONVIF protocol, can provide the SDK.

Optional back-end products for the system:

IE browse software, P2P HD remote monitoring management software (one key realize remote control without complicated settings), Embedded HD NVR, NVR control keyboard, CMS HD network surveillance platform management software, High-definition surveillance analysis software.

Model:		CV-XIP628HW26K	
Camera	Imaging sensor:	8.0MP 4k , H.265+,MStar328Q+Sony 415, 1/2.8" CMOS	
	Scanning mode:	Progressive scanning	
	Illumination:	color 0.001Lux@F1.2,black/white 0.0001Lux@F1.2	
	Lens:	Standard with 8megapixel 4mm,6mm fixed focus CS lens	
	Day and night switch:	IR-CUT dual optical filters auto switch in day and night	
	DNR:	3D-DNR	
	IR source:	42pcs IR Led	
	Effective night vision distance:	40meters (measured value without light condition)	
	P2P	YES	
	Waterproof	YES	
	S/N Ratio	70db	
	HDR	128db	
	WDR	128db	
	Privacy mask	1	
	FTP	YES	
shutter speed	1/(10-10000)s		
Standard compression	Image compression:	H.264	
	Video compression:	H.265+/H.265/H.264,support dual stream,AVI;32Kbps~5Mbps variable;support CBR/VBR	
Image	Max image size:	3840x2160	
	Frame rate:	Main stream:8MP 3840x2160@20fps,6MP 3072x2048@30fps 4MP 2688X1520@30pfs, 3MP 2304x1296@30fps 2.0MP 1920X1080@30fps	
Function	Interface protocol:	HTTP/RTSP/FTP/PPPOE/DHCP/DDNS/NTP/ONVIF2.6/,Hikvision private protocol	
	Intelligent alarm:	Motion detection, shadow alarm, network cable break, IP address conflict	
	POE	YES (optional),IEEE802.3at/af Standard,PoE/IN:37-57V(15.4W), DC/OUT:12V/1A(12.95W)	
	Lightning Protection	Power, network, POE comprehensive lightning protection, in line with national standards GB/T17626.5, the international standard IEC61000-4-5.	
	features	Support WEB configure, support for OSD, support video transmission,support mobile surveillance, support for mobile detection alarm center after the screen pop-up reminders and linkage; supports JPEG capture; provide perfect the SDK development package	
Basic parameter	Power input:	DC 12V±10%	
	Power consumption:	1W (IR off) / 9.5W (IR on)	1.1W / 9.6W (IR on)
	Work environment:	-40℃ ~ 85℃ , humidity is less than 95% (no condensation)	