

Megapixel HD IP IR bullet Camera (42 IR LED)

Model No.: CV-XIP1033GWE



Main feature:

- Professional design for HD network camera, small, beautiful and delicate, best for home security.
- Material: aluminum alloy and plastic, innovative patented heat dissipation structure, make HD camera can works well under high temperature.
- 5.0 megapixel
- Advanced digital signal processing technology, high brightness imported SMT IR source, show the best HD video effects in both day and night environment.
- 5.0 Megapixel HD CS lens+ IR-CUT auto switch in day and night, 2.8-12mm manual zoom Lens
- 42 IR LED, effective night vision distance is 50m, excellent performance in dark environment.
- Support 3D DNR, auto white balance, auto electronic shutter, auto electronic gain, real color reproduction, high resolution image.
- ONVIF protocol, can provide the SDK.

Optional back-end products for the system:

IE browse software, P2P HD remote monitoring management software (one key realize remote control without complicated settings), Embedded HD NVR, NVR control keyboard, CMS HD network surveillance platform management software, High-definition surveillance analysis software.

Technical parameters:

| | | | |
|---------------------------------|---|---|---------------------|
| Model: | | CV-XIP1033GWE | |
| Camera | Imaging sensor: | 5.0MP,H.265+, MStar337DE+4230, 1/2.9" CMOS,Humanoid detection,strong light restrain | |
| | Scanning mode: | Progressive scanning | |
| | Illumination: | color 0.01Lux@F1.2,black/white:0.005Lux@F1.2, IR on 0 lux | |
| | Lens: | 5 megapixel 2.8-12mm manual zoom Lens | |
| | Day and night switch: | IR-CUT dual optical filters auto switch in day and night | |
| | DNR: | 3D-DNR | |
| | IR source: | 42pcs IR Led | |
| | Effective night vision distance: | 50 meters (measured value without light condition) | |
| | P2P | YES | |
| | Waterproof | YES | |
| | WDR | 128db | |
| | S/N Ratio | 50db | |
| | Privacy mask | 1 | |
| | shutter speed | 1/(10-10000)s | |
| FTP | YES | | |
| Standard compression | Image compression: | H.264 | |
| | Video compression: | H.265+/H.265/H.264, support dual-stream, AVI format; support stream 32Kbps ~ 3.5Mbps adjustable;support CBR/VBR | |
| Image | Max image size: | 2592X1944 | |
| | Frame rate: | 2592X1944@25fps,2560x1440@25fps,3MP/2048*1536@20fps、 1080P/720P/D1@25fps | |
| Function | Interface protocol: | HTTP/RTSP/FTP/PPPOE/DHCP/DDNS/NTP/ONVIF2.6/,Hikvision private protocol | |
| | Intelligent alarm: | Humanoid detection,Motion detection, shadow alarm, network cable break, IP address conflict | |
| | POE | YES (optional),IEEE802.3at/af Standard PoE/IN:37-57V(15.4W), DC/OUT:12V/1A(12.95W) | |
| | Lightning Protection | Power, network, POE comprehensive lightning protection, in line with national standards GB/T17626.5, the international standard IEC61000-4-5. | |
| | features | Support WEB configure, support for OSD, support video transmission,support mobile surveillance, support for mobile detection alarm center after the screen pop-up reminders and linkage; supports JPEG capture; provide perfect the SDK development package; | |
| Basic parameter | Power input: | DC 12V±10% | |
| | Power consumption: | 1W (IR off) / 9.5W (IR on) | 1.1W / 9.6W (IR on) |
| | Work | -40℃ ~ 85℃, humidity is less than 95% (no condensation) | |

Te:+86 755 36520814 <http://www.cavisecurity.com>

Add :7/F, Hongyu building, gushu xixiang, baoan district,shenzhen,China

| | | |
|--|---------------------|--|
| | environment: | |
|--|---------------------|--|